





Foam / Chemical Injectors

ST-60.1	ST-60.1 with Coupling	ST-60.1 with Screw Coupling	R+M Foam / Chemical Injectors																												
 <p>3/8" M - 3/8" F. Max. 250 bar / 60 °C. 10 - 16 l/min</p> <table border="1"><tr><td>R+M Nr.</td><td></td></tr><tr><td>200 060 700</td><td></td></tr></table> <p>16 - 21 l/min</p> <table border="1"><tr><td>R+M Nr.</td><td></td></tr><tr><td>200 060 710</td><td></td></tr></table>	R+M Nr.		200 060 700		R+M Nr.		200 060 710		 <p>Coupling KW - plug KW. Suction hose 1 m. Suction filter ST-31</p> <table border="1"><tr><td>R+M Nr.</td><td></td></tr><tr><td>200 060 750</td><td></td></tr></table>	R+M Nr.		200 060 750		 <p>M22 F - M22 M. Suction hose 1 m. Suction filter ST-31</p> <table border="1"><tr><td>R+M Nr.</td><td></td></tr><tr><td>200 060 760</td><td></td></tr></table>	R+M Nr.		200 060 760		 <p>new</p> <p>3/8" M. Stainless steel. Chemical dosage is set by 8 exchangeable nozzle inserts (0.5 - 2 mm). With peak seat. Max. 200 bar / 90 °C</p> <table border="1"><tr><td>R+M Nr.</td><td></td><td></td><td></td></tr><tr><td>541 034 730</td><td>11 - 16 l/min</td><td>2,1 mm</td><td></td></tr><tr><td>541 034 740</td><td>16 - 21 l/min</td><td>2,3 mm</td><td></td></tr></table>	R+M Nr.				541 034 730	11 - 16 l/min	2,1 mm		541 034 740	16 - 21 l/min	2,3 mm	
R+M Nr.																															
200 060 700																															
R+M Nr.																															
200 060 710																															
R+M Nr.																															
200 060 750																															
R+M Nr.																															
200 060 760																															
R+M Nr.																															
541 034 730	11 - 16 l/min	2,1 mm																													
541 034 740	16 - 21 l/min	2,3 mm																													

Easy Foamer ST-5600

The Easy Foamer ST-5600 is especially designed for applications which require only one chemical detergent in combination with a high pressure cleaning of max. 150 bar. The chemical dosage is effected by exchangeable nozzle inserts. The engineering of the Easy Foamer ST-5600 follows the principle of the Turn & Clean ST-5800. Instead of three parallel supplies for chemicals the Easy Foamer ST-5600 is equipped with only one supply.

Easy installation, durable design (stainless steel), excellent foam results and an unbeatable price are the main characteristics of the Easy Foamer ST-5600.



Compressed air pressure 3 - 8 bar. Compr. air pressure flow 30 - 50 l/min

R+M Nr.	water <input type="checkbox"/>	water <input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
205 600 500	20 - 50 bar	max. 20 l/min	3/8" F	1/2" M
205 600 600	50 - 150 bar	max. 25 l/min	3/8" F	1/2" M

Foam Injectors



Stainless steel.
1/4" F - 1/4" M.
Flow at 100 bar

R+M Nr.	<input type="checkbox"/>
541 053 193	13 l/min
108 290 20	34 l/min